

CHEVRON™

SERIES 12 LCG CARRIER



LOW CENTER OF GRAVITY

STANDARD EQUIPMENT

- Aluminum or Steel Body
- Aluminum Body:
 - heavy duty extruded sill with integral full length graphite-impregnated wear strips top and bottom
 - front left and right chain trays
 - extruded double-box sides
 - rear sill reinforcements
 - 4 rear and 2 front chain locks
 - 102 in. wide body
- Steel Body:
 - 3/16 smooth floor or 3/16 deck plate
 - front left and right chain trays
 - 3 x 2 Corten tube crossmembers - 8 inches O.C.
 - 4 rear and 2 front chain locks
 - black body paint
 - 102 in. wide body
- Releasable L-arm wheel retainers
- Mechanical anti-tilt
- Inboard tilt cylinders
- Fully hydraulic wheel lift
- Illuminated dual controls
- 2 side body marker lights per side
- Body lock with nylatron roller bearings
- Mudflaps
- Federal standard 108 lighting
- Tow light plug
- Water resistant junction box for wire harness connection
- Lubrication fittings on all pivot points
- 9,000 lb. Planetary low mount winch
- Pilot operated holding valves on tilting and lifting functions
- Back up alarm
- Direct mount pump - 18 GPM
- Cable tensioner
- Cable roller guide
- Winch clutch free spool extension handle
- Four safety chains
- LED lights

OPTIONAL EQUIPMENT

- Removable steel side rails
- Floor level sides with stake pockets
- Polished aluminum removable blade sides
- Trailer style rub rails
- Additional chain locks
- 12,000 lb. low mount Planetary winch
- Model JXL cab protector with aluminum trim
- Model F cab protector - perimeter steel tube
- Frame mount narrow base pylon
- Frame mount tri-box pylon
- PTO
- Retractable ladder
- Factory installation
- Steel body paint (other than black)
- Pivoting L-arms
- AutoGrip™ II wheel lift
- Hydraulic stabilizer
- Galvanized subframe
- Winch clutch air free spool
- Dual control winch clutch air free spool
- Wired remote control
- Radio remote control
- Manual SlideWinder

Chevron reserves the right to improve or upgrade its products without obligation to modify previously manufactured units. This publication is printed in the U.S.A. and is the exclusive property of Chevron, Inc.

ACCESSORIES

- Bar light
- Work lights
- Switch panel
- Magnetic tow lights
- J-hook chains
- V-chain
- Trailer ball plate
- Trailer hitch for AutoGrip™ II
- Aluminum tool box (33L x 18H x 18D)
- Aluminum tool box (49L x 18H x 18D)
- Aluminum tool box (65L x 18H x 18D)

CHASSIS RECOMMENDATIONS

- Minimum GVWR - 19,000 - wheel lift
- Maximum GVWR - 25,500
- Accessible PTO opening
- Maximum frame height - 38 inches
- Recommended frame height - 35 inches
- Minimum frame RBM each rail - 600,000 in • lbs.

CARRIER LENGTH	USABLE CAB-TO-AXLE
21	138
21.5	144
22	150

SPECIFICATIONS

Aluminum Body Width	102 O.D. - 98 I.D.
Steel Body Width	102 O.D. - 96 I.D.
Body Extension	117 inches
Control Valve	Sectional, 20 GPM, 2000 PSI
Oil Reservoir	12 gallons
Oil Filter	250 PSI, 10 Microns
Pump	18 GPM

Body Rating*	12,000 lbs. evenly distributed
Wheel Lift Rating*	4,000 lbs. extended

** Load ratings are based on structural factors - not chassis capability or capacity.*

Patents: Releasable L-arm #4,875,822 Independent Wheel Lift #1B 5,061,147
AutoGrip II #5,692,871



Distributed By:

Chevron, Inc.
7320 W. Market Street • U.S. Route 62 • Mercer, PA 16137
(724) 981-7500 • Toll Free (800) 886-6400 • FAX (724) 981-4425
www.chevroninc.com