



**Pblt Of Atlanta, Llc (P801)**  
**172 Van Mar Blvd.**  
**Jackson, Georgia 30233**

**Miller Industries**  
**8503 Hilltop Dr**  
**Ooltewah, Tennessee 37363**  
**United States of America**

**David Marshall**  
**Cell Phone:**  
**Office Phone: (404)592-9980**  
**Email: dmarshall@peteatlanta.com**

**VINCE TIANO**

## Vehicle Summary

	<b>Unit</b>		<b>Chassis</b>	
Model:		Model 536	Fr Axle Load (lbs):	10000
Type:		Full Truck	Rr Axle Load (lbs):	20000
Description 1:		2024 MLR 536 144	G.C.W. (lbs):	26000
Description 2:		144 CA		
	<b>Application</b>		Road Conditions:	
Intended Serv.:		City Delivery	Class A (Highway)	100
Commodity:		Other Commodity	Class B (Hwy/Mtn)	0
	<b>Body</b>		Class C (Off-Hwy)	0
Type:		Flatbed	Class D (Off-Road)	0
Length (ft):		20	Maximum Grade:	6
Height (ft):		13.5	Wheelbase (in):	212
Max Laden Weight (lbs):		1000	Overhang (in):	81.8
			Fr Axle to BOC (in):	67.5
			Cab to Axle (in):	144.5
	<b>Trailer</b>		Cab to EOF (in):	226.3
No. of Trailer Axles:		0	Overall Comb. Length (in):	333.8
Type:				
Length (ft):		0	<b>Special Req.</b>	
Height (ft):		0		
Kingpin Inset (in):		0		
Corner Radius (in):		0		
	<b>Restrictions</b>			
Length (ft):		40		
Width (in):		102		
Height (ft):		13.5		

**Approved by:** \_\_\_\_\_

**Date:** \_\_\_\_\_

**Note: All sales are F.O.B. designated plant of manufacture.**



Sales Code	Std/Opt	Description	\$ List	Weight
<b>Base Model</b>				
0005361	S	<b>Model 536</b> The Model 536 is the ultimate Class 6 medium duty. It is highly adaptable and can be configured up to 26,000 lbs. to meet the demands of a variety of medium-duty applications. Combining durability and power with options to match the needs of both the job and driver, the 536 is an exceptional performer and ideal for refrigerated van, pickup and delivery, wrecker and municipal utility applications.	96,375	9,470
0091200	S	<b>Other Commodity</b>	0	0
0093340	S	<b>City Delivery</b> Truck or tractor which hauls freight, typically operating within a 100-mile radius, on public streets and highways and other paved surfaces. Typically includes package and freight delivery.	0	0
0095020	O	<b>Flatbed</b>	0	0
0098170	S	<b>United States Registry</b> Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
<b>Configuration</b>				
0200700	S	<b>Not Applicable</b> Secondary Manufacturer	0	0
0210260	S	<b>Class 6 Chassis Weight Rating 26,000 lb GVWR</b>	0	0
<b>Frame &amp; Equipment</b>				
0515020	O	<b>10-5/8" Steel Rails 286-325"</b> 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	340	427
0611300	O	<b>Heavy Duty 5-Piece Crossmember BOC IPO Standard</b> Class 5, 6, 7	17	20
0611350	S	<b>1-Piece Steel Frame Rail Xmbr</b> Excludes Suspension	0	0
0612230	O	<b>Custom Wheelbase or Overhang</b> Engineering approval may be required.	350	0
0644090	S	<b>EOF Square without Crossmember</b> End-of-frame square without crossmember. For use with body builder installed crossmember.	0	0
0651090	S	<b>Omit Rear Mudflaps and Hangers</b>	0	0
<b>Front Axle &amp; Equipment</b>				
1011830	O	<b>Dana Spicer E1002IL 10,000 lb, 3.5 in. Drop</b> Axle is designed for applications with a gross axle weight rating (GAWR) of 10,000 pounds. The axles have exclusive one-piece forged	116	0

Price Level: January 1, 2022

100% Complete

Date: September 18, 2022

Deal: 2024 MLR 536 144

Quote Number: QUO-1005420-T3Q7G8

Printed On: 9/18/2022 3:49:40 PM



Sales Code	Std/Opt	Description	\$ List	Weight
		design knuckle including steer arm, tie rod arm and spindle. This feature helps in greater durability and reduced maintenance.		
1111155	S	<b>Mono-Leaf Springs, Shocks, 10,000 LBS.</b>	0	0
1243040	S	<b>Power Steering Sheppard HD94</b> Sheppard HD94 power steering gear is a light weight version of heavy duty line-haul power steering gear. For use with 10,000 to 13,200 lb. axle ratings.	0	0
1250180	O	<b>Power Steering Reservoir Frame Mounted</b> The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1353540	O	<b>PHP10 Aluminum PreSet PLUS Hubs</b> PHP10 aluminum PreSet PLUS hubs have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug on drive and trailer hubs for inspection of metal particles in lubricant, with a long life oil seal and bearings are pre-adjusted. Use with Front Axle.	36	-18
1380240	O	<b>Dana Spicer Wide Track IPO Standard</b> Dana Spicer wide track front axles offer added stability and deliver greater turn angles. 71in KPI IPO 69in for E1202, E1322, E1462, D2000F front axles.	94	15
1380260	O	<b>Bendix Air Cam Front Drum Brakes 16.5x5</b> For use with 10,000 lbs to 14,600 lbs steer axles. Includes automatic slack adjusters & outboard mounted brake drums.	-53	0
1391410	O	<b>Gusseted Cam Brackets, Steer Axle</b>	0	0
1391470	U	<b>5 MM FRONT SPRING SPACER BLOCKS</b>	0	0
<b>Rear Axle &amp; Equipment</b>				
1513260	O	<b>Dana Spicer P20060S 20,000 lb</b>	1,799	-97
1616290	O	<b>PHP10 Aluminum PreSet PLUS Hubs</b>	52	0
1680490	O	<b>Gusseted Cam Brackets, Drive Axle(s)</b>	26	2
1680500	S	<b>SBM Valve</b> Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0	0
1680950	S	<b>Stability System Not Selected Or Not Available</b>	0	0
1682430	S	<b>Anti-Lock Braking System (ABS) 4S4M</b> ABS-6. Includes air braking system.	0	0
1684200	S	<b>Synthetic Axle Lubricant All Axles</b> Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the	0	0

Price Level: January 1, 2022

100% Complete

Date: September 18, 2022

Deal: 2024 MLR 536 144

Quote Number: QUO-1005420-T3Q7G8

Printed On: 9/18/2022 3:49:40 PM



Sales Code	Std/Opt	Description	\$ List	Weight
		lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.		
1687020	O	<b>Bendix Air Cam Rear Drum Brakes 16.5x8.6</b> Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums. Refer to TSB 11-57 for more information.	98	5
1704880	O	<b>Ratio 4.88 Rear Axle</b>	0	0
1811140	O	<b>Peterbilt Low Air Leaf 21,000 lb, Light Weight</b>	198	-175
1922260	O	<b>Dash Mtd Dump Switch with Indicator Light</b> Dash mounted dump switch with indicator light for suspension.	29	2

### Engine & Equipment

2073306	O	<b>PACCAR PX-7 300@2600 GOV@2600 660@1600 PERFORMANCE (2021 EMISSIONS)</b>	2,142	0
		N21350 C121 75...Maximum Accelerator Pedal Ve N21370 C128 75...Maximum Cruise Speed (P059) N21460 C132 1400..Max PTO Speed (P046) N21520 C133 600...Timer Setting (P030) N21610 C188 40....Low Ambient Temperature Thre N21620 C189 60....Intermediate Ambient Tempera N21630 C190 80....High Ambient Temperature Thr N21550 C206 35....Engine Load Threshold (P516) N21340 C209 120...Hard Maximum Speed Limit (P1 N21510 C225 NO....Enable Idle Shutdown Park Br N21450 C231 NO....Gear Down Protection (P026) N21570 C233 YES...Idle Shutdown Manual Overrul N21440 C234 NO....Engine Protection Shutdown ( N21480 C238 NO....Auto Engine Brake in Cruise N21470 C239 NO....Cruise Control Auto Resume ( N21430 C333 0.....Reserve Speed Limit Offset ( N21410 C334 0.....Maximum Cycle Distance (N202 N21590 C382 YES...Enable Hot Ambient Automatic N21500 C395 0.....Expiration Distance (N209) N21530 C396 YES...Enable Impending Shutdown Wa N21540 C397 60....Timer For Impending Shutdown N21320 C399 120...Standard Maximum Speed Limit N21400 C400 252...Reserve Speed Function Reset N21420 C401 10....Maximum Active Distance (N20 N21330 C402 0.....Expiration Distance (N207)		
2091130	S	<b>VMUX Electronics Architecture</b>	0	0
2091310	O	<b>Engine Idle Shutdown Timer Disabled</b>	0	0
2091315	O	<b>Enable EIST Ambient Temp Override</b>	0	0

Price Level: January 1, 2022

100% Complete

Date: September 18, 2022

Deal: 2024 MLR 536 144

Quote Number: QUO-1005420-T3Q7G8

Printed On: 9/18/2022 3:49:40 PM



Sales Code	Std/Opt	Description	\$ List	Weight
2091372		<b>Eff EIST NA Expiration Miles</b>	0	0
2091640		<b>Effective VSL Setting NA</b>	0	0
2092018	O	<b>Typical Operating Speed 75 MPH</b>	0	0
2092033	O	<b>Powertrain Optimized for Balance</b> Best analysis for vehicles where service includes frequent start and stop cycles.	0	0
2140200	O	<b>CARB Engine Idling Compliance</b> PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2140320	O	<b>Remote Throttle &amp; Wiring EOF</b> Excludes Can Communication	82	4
2140450	O	<b>Remote PTO/Throttle, 12-Pin</b> Eng Bay Remote Control Provision	54	0
2140660	O	<b>CARB Emission Warranty</b>	0	0
2513060	S	<b>PACCAR 160 Amp Alternator, Brushed</b> PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2521090	O	<b>Immersion Type Block Heater 110-120V</b> Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	82	2
2522110	O	<b>PACCAR 12V Starter, N/A PACCAR MX Engines</b> PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0	0
2538020	O	<b>2 PACCAR Premium 12V Dual Purpose Batt 1460 CCA</b> Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	12	0
2539700	O	<b>Battery Jumper Terminal</b> Mtd under hood RH frame rail. Available with PX-7 engines only.	110	4
2621090	S	<b>DM Advantage ON/OFF Fan Clutch</b> Horton DM Advantage Two-Speed Fan Clutch On/Off for heavy-duty, medium-duty and a variety of off-highway equipment.	0	0
2723210	S	<b>18.7 CFM Air Compressor</b> N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2812210	S	<b>VGT Exhaust Brake</b> (Variable Geometry Turbo). Provides approximately 90-100 HP of retardation and is part of the turbocharger.	0	0
2921110	S	<b>PACCAR Fuel/Water Separator Standard Service</b> PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	0	0

Price Level: January 1, 2022

100% Complete

Date: September 18, 2022

Deal: 2024 MLR 536 144

Quote Number: QUO-1005420-T3Q7G8

Printed On: 9/18/2022 3:49:40 PM



Sales Code	Std/Opt	Description	\$ List	Weight
2921210	S	<b>No Fluid Heat Option for Fuel Filter</b>	0	0
2921320	O	<b>12V Heat for Fuel Filter</b> Fuel filter heaters help ensure a seamless flow of diesel from the tank to the combustion chamber. Eliminating any possibility of moisture freezing within the fuel filter while simultaneously increasing the fuel temperature for atomization within the engine.	61	0
3010400	O	<b>Engine Protection Shutdown w/ Label</b> Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	5	0
3114270	S	<b>High Efficiency Cooling System</b> Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 367 1325 sq in, 367 HH Fepto 1325 sq in, 365 Fepto 1183 sq in, 365 Full Frame Extension 1000 sq in, 520 1202 sq in, 579 1456.9 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 389/367 HH 1604 sq in, 365/567 1379 sq in.	0	0
3211140	S	<b>(1) Air Cleaner Engine Mounted</b>	0	0
3365290	S	<b>Exhaust Single RH Horizontal</b> DPF/SCR RH Under Frame.	0	0
<b>Transmission &amp; Equipment</b>				
4051710	O	<b>Allison 2500 RDS-P Transmission, Gen 5</b> Rugged Duty Series. Includes Allison Shift Performance, Mobil Delvac Automatic Transmission Fluid, and Water-Oil Heat Exchange. Also includes dash mounted indicator light when the transmission fluid, filter or clutches need service. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-3.51, 2nd-1.90, 3rd-1.44, 4th-1.00, 5th-0.74, 6th-0.64. Reverse ratios: DR-(5.09).	2,752	133
4210940	O	<b>SPL100 Driveline, 2 Midship Bearings</b>	1,630	60
4230090	O	<b>PTO F/O Muncie</b>	0	0
4233910	O	<b>(1) Dash Mounted Single Acting EOH PTO Control</b> Electric-over-hydraulic, spec'ing PTO switch does not ensure the PTO will fit. Sends signal to Allison to engage PTO.	89	1
4252890	O	<b>Allison FuelSense 2.0 Not Desired</b>	0	0
4252950	O	<b>Omit Allison Neutral At Stop</b>	0	0
4256880	O	<b>Allison 6-Speed Configuration</b> Wide ratio gears, 2500 series transmissions.	0	0
4256920	O	<b>Dash Mounted Push Button Shifter</b>	513	3

Price Level: January 1, 2022

100% Complete

Date: September 18, 2022

Deal: 2024 MLR 536 144

Quote Number: QUO-1005420-T3Q7G8

Printed On: 9/18/2022 3:49:40 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
		Available with Allison transmissions		
4257110	O	<b>LH Mounted Trans PTO Provisions</b>	35	0
<b>Air &amp; Trailer Equipment</b>				
4510190	S	<b>Bendix AD-HF Air Dryer, Heater</b> Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	0	0
4520420	O	<b>Pull Cords All Air Tanks</b>	6	0
4540420	S	<b>Nylon Chassis Hose</b>	0	0
4543320	S	<b>Steel Painted Air Tanks</b> All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4611930	O	<b>Body Connections 5' BOC</b> Junction box contains light and power circuits for body connections located 5' from back-of-cab	82	4
<b>Tires &amp; Wheels</b>				
5058000	O	<b>FF: MN 16ply 255/70R22.5 XZE</b> Efficiency Rating: Poor All-position radial with extra-wide, extra-deep tread designed to help deliver wear in high scrub regional and line haul applications. Diameter = 36.7 inches; SLR = 17.2 inches. Compares to Goodyear G149 RSA and Bridgestone R250F tread.	203	-40
5107420	O	<b>RR: CN 16ply 255/70R22.5 HDR</b> Efficiency Rating: Fair	518	-68
5190004	O	<b>Code-rear Tire Qty 04</b>	0	0
5220720	O	<b>FF: Alcoa ULT397 22.5X8.25 High Polish</b> Aluminum. Built for heavy-duty applications and are light weight. Available with polished and Dura-Bright finishes.	296	-50
5320720	O	<b>RR: Alcoa ULT397 22.5X8.25 High Polish</b> Aluminum. Built for heavy-duty applications and are light weight. Available with polished and Dura-Bright finishes.	592	-100
5390004	O	<b>Code-rear Rim Qty 04</b>	0	0
5409680	O	<b>Schrader Double Sealing Extensions</b> Schrader on tire valve extensions provide a seal against contaminants while extending the valve mouth for convenient access. Fits standard .305-32" valve cap threads. Maximum operating pressure, 150 psi.	33	0

Price Level: January 1, 2022

100% Complete

Date: September 18, 2022

Deal: 2024 MLR 536 144

Quote Number: QUO-1005420-T3Q7G8

Printed On: 9/18/2022 3:49:40 PM



Sales Code	Std/Opt	Description	\$ List	Weight
<b>Fuel Tanks</b>				
5584040	O	<b>D-Shaped Aluminum 50 Gallon Fuel Tank LH U/C</b> Non-slip step LH under cab	79	-10
5602050	O	<b>Location LH U/C 50 Gallon</b>	0	0
5650540	O	<b>Polish (1) Non-Slip Fuel Tank Step, U/C Tank Only</b>	30	0
5650810	O	<b>Polish (1) Aluminum Fuel Tank</b>	199	0
5652830	O	<b>Polish All Fuel / Hydraulic Tank Straps</b> Does not apply to rectangular DEF tank straps	2	0
5652900	O	<b>DEF Tank Mounted LH Under Cab</b>	91	0
5652990	O	<b>DEF To Fuel Ratio 2:1 Or Greater</b>	0	0
5653000	O	<b>Polished Stainless Steel Cover For DEF Tank</b>	176	0
5655019	S	<b>DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal</b>	0	0
<b>Battery Box &amp; Bumper</b>				
6020040	O	<b>MD Battery Box, Non-Slip Step RH Under Cab</b>	122	0
6030150	O	<b>Rubber Battery Pad In Bottom of (1) Battery Box</b> Mat in box that holds batteries only	11	4
6030540	O	<b>Polish Battery/Tool Box(s), Aftertreatment Cab</b> Entry complete	437	0
6030630	O	<b>Aluminum Battery Box Cover</b>	123	4
6121020	O	<b>Aero Bumper, Steel 3-Piece, Bright Finish</b> ***Warning*** Due to a new legal regulations, all New Medium Duty trucks require headlights to be located in the bumper when the chassis height is GREATER than the following chassis height:  Measurement to bottom of frame at front of frame: for the 107 Aero Hood 32.6, for the 109 Aero Hood 31.4, for the 109 Vocational Hood 26.7. Work with applications if your chassis height is unacceptable.	1,084	20
<b>Cab &amp; Equipment</b>				
6510150	S	<b>Aerodynamic 107in BBC Aluminum Cab &amp; SMC Hood</b> With molded charcoal crown.	0	0
6540160	O	<b>Thermal Insulation Package in Cab</b> The thermal insulation package is designed to make the cab thermally efficient in extreme temperatures. The model 520 adds insulation surrounding the doghouse to reduce engine heat transmitted to the cab.	67	2
6540740	O	<b>Peterbilt Keyless Entry</b>	211	2

Price Level: January 1, 2022

100% Complete

Date: September 18, 2022

Deal: 2024 MLR 536 144

Quote Number: QUO-1005420-T3Q7G8

Printed On: 9/18/2022 3:49:40 PM





Sales Code	Std/Opt	Description	\$ List	Weight
		The Peterbilt key fob functions to lock or unlock the vehicle. With a single click, the drivers door is locked or unlocked and with a double click all doors are locked or unlocked. The third button, depicted by a picture of a lamp, will start the exterior light self-test sequence, helpful when performing the daily pre-trip inspection.		
6800180	O	<b>Hood Crown - Bright Finish ipo Molded Gray</b>	89	0
6917320	S	<b>Seats Inc. Driver Seat</b>	0	0
6923160	S	<b>(2) Person Passenger Seat</b>	0	0
6930500	O	<b>Drivers Armrest - RH Only</b>	28	2
6939110	S	<b>Toolbox Under Passenger Seat</b> Non-Suspension Seat	0	0
6939400	S	<b>Air Ride Driver</b>	0	0
6939420	O	<b>High Back Driver</b>	44	0
6939470	S	<b>Vinyl Driver</b>	0	0
6939510	S	<b>Non-Air Ride Passenger</b>	0	0
6939540	S	<b>Low Back Passenger</b>	0	0
6939570	S	<b>Vinyl Passenger</b>	0	0
7000025	O	<b>Steering Wheel With Multi-Function</b> Includes Peterbilt logo on horn button , audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	246	4
7000065	O	<b>Metal Interior Door Panel Kick Plates</b>	67	2
7001520	S	<b>Adjustable Steering Column - Tilt/Telescope</b>	0	0
7036130	O	<b>Probilt Interior Grey/Black - Curved Roof</b>	176	0
7110680	O	<b>Exterior Cab Entry Grabhandle</b> Textured; NFPA compliant. Available on Day Cab specifications only.	169	0
7210420	O	<b>Dark Window Tint IPO Standard Tint - Day Cab</b>	18	0
7210510	O	<b>3-Piece Glass Rear Cab Window, All Pieces Fixed</b>	157	12
7210540	S	<b>Day Cab Rear Window</b> Day cab rear window flush to back of cab.	0	0
7230060	S	<b>1-Piece Curved Windshield</b>	0	0
7230360	S	<b>Power Door Locks and Power Window Lifts</b> Standard	0	0

Price Level: January 1, 2022

100% Complete

Date: September 18, 2022

Deal: 2024 MLR 536 144

Quote Number: QUO-1005420-T3Q7G8

Printed On: 9/18/2022 3:49:40 PM



Sales Code	Std/ Opt	Description	\$ List	Weight
7322010	S	<b>Combo Fresh Air Heater/Air Conditioner</b> With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7410040	O	<b>Outside Sunvisor - Stainless Steel</b> Not available with 2.1M high roof sleeper.	250	4
7510060	O	<b>Aero Rear View Mirror Housing, Bright Finish</b>	173	3
7514010	O	<b>Peterbilt Aero Rear View Mirror, Motorized</b> Includes top mirror with motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	257	3
7514050	S	<b>Look Down Mirror Over Passenger Door</b> with Black Housing	0	0
7620040	O	<b>(2) Air Horns Round, 26" Length</b> Roof mounted. Round horn shield.	278	16
7721050	O	<b>Satellite Radio</b> Requires USB port and bluetooth for phone and audio.	222	0
7722120	O	<b>ConcertClass, AM/FM, Weatherband, 3.5 Aux</b>	331	11
7725710	O	<b>Standard Speaker Package For Cab</b> (2) Speakers	50	4
7728030	O	<b>Radio Mute When In Reverse</b> For automatic or automated transmission	0	0
7728040	O	<b>Bluetooth Phone and Audio Requires USB Port</b>	38	0
7728050	O	<b>USB Port</b>	38	0
7788055	O	<b>SmartLINQ Remote Diagnostics</b> SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine.	0	0
7788057	O	<b>24 Months SmartLINQ Subscription</b> PACCAR PX Engines.	0	0
7851480	S	<b>Peterbilt Electric Windshield Wipers</b> With Intermittent Feature.	0	0

Price Level: January 1, 2022

100% Complete

Date: September 18, 2022

Deal: 2024 MLR 536 144

Quote Number: QUO-1005420-T3Q7G8

Printed On: 9/18/2022 3:49:40 PM



Sales Code	Std/Opt	Description	\$ List	Weight
7852050	O	<b>Auto Reset Circuit Protection</b> Daycab and Sleeper	19	0
7852060	S	<b>Solid Rear Day Cab Mounts</b>	0	0
7852090	O	<b>Cigar Lighter and Ash Cup</b> Mounted in dash.	59	2
7900090	O	<b>Triangle Reflector Kit, Ship Loose</b> Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	18	13
7900310	O	<b>Fire Extinguisher, Mounted Outboard Driver Seat</b> Hazmat approval UL listed/rated ABC	56	9
7900950	O	<b>Backup Alarm Wiring To BOC, 5 Ft Additional Wire</b>	28	6
8011850	O	<b>Transmission Oil Temperature (Main)</b> Located in Digital Cluster Display.	24	0
8021380	S	<b>Air Restriction Indicator</b> Mounted on air cleaner, intake piping, or firewall	0	0
8021810	O	<b>Brake Application Air Pressure (Tractor)</b> Located in Digital Cluster Display.	0	0
8021860	O	<b>Suspension Air Pressure 1 (Load)</b> Located in Digital Cluster Display	133	0
8070390	O	<b>Engine Hourmeter Gauge</b> Located in Digital Cluster Display	0	0
8070450	O	<b>Engine PTO Hourmeter Gauge</b> Located In Digital Cluster Display	0	0
8070810	O	<b>Engine Manifold Pressure (Turbo Boost)</b> Located in Digital Cluster Display	0	0
8070820	O	<b>Engine Percent Torque</b> Located in Digital Cluster Display	0	0
8070860	S	<b>Main Instrumentation Panel</b> Digital Cluster 7" Display includes: Physical (Analog) - Speedometer, Tachometer, Oil Pressure, Coolant Temp and Display Gauges - Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure for air brake trucks.	0	0
8070940	O	<b>Voltmeter Gauge (MD/520 Only)</b> Located in Digital Cluster Display	0	0
8076110	O	<b>(5) Additional Dash Switches, Wiring</b> At BOC/BOS	322	4
8111110	S	<b>Headlights Composite Fender Mounted</b> Integral park, turn, and side marker	0	0
8120980	S	<b>(5) Marker Lights, Aero LED</b>	0	0
8131560	O	<b>(2) Peterbilt Fog Lights</b> Recessed in bumper	262	6
8134160	S	<b>Self-Canceling Turn Signal</b>	0	0
8140120	O	<b>Incandescent Square Stop/Turn/Tail/Backup</b> Left-hand / right-hand square end of frame or dropped a-brace	-2	9

Price Level: January 1, 2022

100% Complete

Date: September 18, 2022

Deal: 2024 MLR 536 144

Quote Number: QUO-1005420-T3Q7G8

Printed On: 9/18/2022 3:49:40 PM



Sales Code	Std/Opt	Description	\$ List	Weight
<b>Paint</b>				
8500710	O	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A- L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0	0

<b>Shipping Destination</b>				
<b>Options Not Subject To Discount</b>				
9400091	S	Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km	0	0
9400093	S	PACCAR PX-7 Standard Coverage 3 years/Unlimited Miles/Unlimited hrs	0	0
9408702	O	Base Warr: Emissions (CARB Surcharge) 5YR/150K MI - PX-7 Engine	1,084	0
9408931	O	PDI At Excellence Peterbilt Location	230	0
9408936	O	Frame Layout Identical to Previous Chassis Narr 763154	475	0

<b>Miscellaneous</b>				
9409041	S	Aero Hood (MODEL 536)	0	0
9409055	O	State Registry: California	0	0

**Promotions**

**Order Comments**

<b>Total List Price (W/O Freight &amp; Warranty &amp; Surcharges )</b>	\$114,756
<b>Marketing and Service Support Fee</b>	\$770
<b>Prepaid Freight</b>	\$3,525
<b>Total Surcharge/Options Not Subject To Discount</b>	\$1,789
<b>Total Weight</b>	9,736



## Prices and Specifications Subject to Change Without Notice.

---

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

### **PRICING DISCLAIMER**

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*



**Shipping Destinations**

**Intermediate Destination:** PDI At Excellence

Final Destinations	Quantity

\$100,550.00/unit