



Pbtl Of Atlanta, Llc (P801)
172 Van Mar Blvd.
Jackson, Georgia 30233

Miller Industries
8503 Hilltop Dr
Ooltewah, Tennessee 37363
United States of America

David Marshall
Cell Phone:
Office Phone: (404)592-9980
Email: dmarshall@peteatlanta.com

VINCE TIANO

Vehicle Summary

Unit		Chassis	
Model:	Model 589 Traditional	Fr Axle Load (lbs):	18180
Type:	Full Truck	Rr Axle Load (lbs):	46000
Description 1:	27 MODA 589 SLPR 200	G.C.W. (lbs):	85000
Description 2:	V70 MODA		
Application		Road Conditions:	
Intended Serv.:	Wrecker	Class A (Highway)	100
Commodity:	Transportation Equipment	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	9
Type:	Wrecker	Wheelbase (in):	332
Length (ft):	22	Overhang (in):	90.3
Height (ft):	13.6	Fr Axle to BOC (in):	90.1
Max Laden Weight (lbs):	1000		
Trailer		Cab to Axle (in):	241.9
No. of Trailer Axles:	0	Cab to EOF (in):	332.2
Type:		Overall Comb. Length (in):	453.3
Length (ft):	0	Special Req.	
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
Base Model				
0005891	S	Model 589 Traditional Peterbilt is proud to introduce the Legendary Model 589. The Model 589 takes cues from heritage designs and incorporates essential customer feedback to create this legendary and luxurious truck. The Peterbilt Model 589 has a bold, distinctive style and iconic exterior features such as the aluminum hood, wrap-around grille crown with triple bars and 15" stainless steel external air cleaners. A driver centric and luxurious cabin features purposeful storage throughout, automatic climate control and plenty of available brightwork. The interior of the Model 589 provides best-in-class quality and driver comfort.	224,758	14,820
0091170	O	Transportation Equipment	0	0
0093110	O	Wrecker Truck with recovery body used for recovering and towing stranded vehicles and equipment.	0	0
0095250	O	Wrecker	0	0
0098010	O	California Registry California Registry Required for all vehicles that will be registered in the State of California.	0	0
Configuration				
0200700	S	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0514080	O	10-3/4" Steel Rails 403-444" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	1,155	762
0601500	O	Full Steel Inner Liner	2,081	919
0611250	O	Heavy-Duty Iron Front Spring Brackets With Front Air Leaf the front spring bracket is iron but not the shackle bracket	493	35
0611330	O	Zinc Coated Anti Corrosion Treated Frame Rails Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.	387	4
0611790	S	Aluminum Frame Rail Crossmembers Excludes suspension	0	0
0620500	O	Frame Components Bolted IPO Huck Fastened	81	0
0633405	O	Additional Frame Drilling	643	0
0644090	O	EOF Square without Crossmember	62	-64

Price Level: August 1, 2025

100% Complete

Date: February 03, 2026

Deal: 27 MODA 589 SLPR 200

Quote Number: QUO-1235499-B9W2Q5

Printed On: 2/3/2026 2:46:18 AM



Sales Code	Std/Opt	Description	\$ List	Weight
		End-of-frame square without crossmember. For use with body builder installed crossmember.		
0651090	O	Omit Rear Mudflaps and Hangers	-58	-25
Front Axle & Equipment				
1011890	O	PACCAR FX-20 Steer Axle 20,000 lbs. 4" Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 20,000 pounds. Front axle is designed for demanding applications such as construction, heavy haul, refuse, and other vocational uses. Robust forged steel beam construction for long-lasting performance. It utilizes innovative tapered kingpin roller bearings for more efficient operation and improved steering efficiency.	2,865	137
		The PACCAR Steer Axle comes standard with the PACCAR warranty of 5 years, 750,000 miles.		
1114030	O	Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks.	920	119
1233110	O	Power Steering TRW THP60 Dual Gear For use with 16,000 to 20,000 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	1,750	54
1250250	O	Power Steering Reservoir Frame Mounted w/Cooler A power steering cooler helps reduce the heat of the power steering fluid. This is commonly used with systems that may experience more stress from towing or off-road driving.	195	2
1354850	O	PHP10 Iron PreSet PLUS Hubs - Air Disc Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	-158	42
1354870	O	Severe Service Disc Brake Rotor For refuse applications, providing the braking torque necessary to slow or stop the vehicle.	360	97
1380070	O	Greasable Front Spring Pins	69	0
1380290	O	Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	28	0
1380380	S	Tenneco Shocks For Steer Axle Integrated front suspension to suit heavy duty truck market, combining the air spring and the damper into one module.	0	0
1380490	O	PACCAR FX Wide Track IPO Standard 71in KPI IPO 69in front axle for improved turning radius.	0	15
1391380	U	10mm Front Springs Spacer Blocks	0	0
Rear Axle & Equipment				
1523440	O	Dana Spicer D46-172 46,000 LBS	5,347	521

Price Level: August 1, 2025

100% Complete

Date: February 03, 2026

Deal: 27 MODA 589 SLPR 200

Quote Number: QUO-1235499-B9W2Q5

Printed On: 2/3/2026 2:46:18 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		Dana Spicer D46-172 46,000 lbs tandem drive axles offer efficiency improvement, axle weight reduction and reduced lube quantity.		
1616305	O	PHP10 Iron Preset + Hubs - Air Disc	1,715	0
1616310	O	Severe Service Disc Brake Rotor Severe Service Disc Brake Rotor for refuse applications.	-124	14
1680155	O	Bendix Piston Park Brake Chambers For Disc Brakes	1,416	0
1680500	O	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	275	0
1680950	O	Stability System Not Selected Or Not Available	-7	0
1682430	O	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	-137	-30
1683245	S	Tire Pressure Monitoring System	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687040	O	Air Disc Rear Brakes, Tandem Drive Axle Includes Automatic Slack Adjusters.	358	0
1687090	O	Diff Lock Tandem Axles With Speed Interlock. Automatically Disengages Wheel Diff Lock at Speeds Above 25 mph.	2,004	60
1703910	O	Ratio 3.91 Rear Axle	0	0
1821640	O	Peterbilt Air Trac 46,000 lbs, 54in Axle Spacing Light Weight	1,629	291
1920385	O	Air Springs, Internal Bumpers Air Trac / Air Leaf suspensions	54	0
1920450	O	Locate Single Leveling Valve Forward Drive Axle of Peterbilt Air Suspension (not avail with Low Air Leaf Susp or Low Low Air Leaf Susp)	27	0
1922260	O	Dash Mtd Dump Switch with Indicator Light Dash mounted dump switch with indicator light for suspension.	66	2
Engine & Equipment				
2059218	O	X15 565V@1950 GOV@2000 1850@1000 Productivity Series (2024 Emissions)	16,621	428

Price Level: August 1, 2025

100% Complete

Date: February 03, 2026

Deal: 27 MODA 589 SLPR 200

Quote Number: QUO-1235499-B9W2Q5

Printed On: 2/3/2026 2:46:18 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		N21350 C121 75....Maximum Accelerator Vehicle		
		N21370 C128 75....Maximum Cruise Control Speed		
		N21460 C132 1100..PTO Maximum Engine Speed		
		N21520 C133 600...Idle Shutdown Timer		
		N21610 C188 39....Idle Shutdown Cold Ambient A		
		N21620 C189 60....Idle Shutdown Intermediate A		
		N21630 C190 80....Idle Shutdown Hot Ambient Ai		
		N21550 C206 35....Idle Shutdown Percent Engine		
		N21340 C209 100...Maximum Vehicle Speed		
		N21510 C225 NO....Idle Shutdown with Parking B		
		N21450 C231 NO....Gear Down Protection		
		N21570 C233 YES....Idle Shutdown Manual Overrid		
		N21440 C234 NO....Engine Protection Shutdown		
		N21480 C238 NO....Cruise Control and Engine Br		
		N21470 C239 NO....Cruise Control Auto-Resume		
		N21430 C333 0.....Driver Initiated OverrideMax		
		N21410 C334 0.....Driver Initiated Override Ma		
		N21590 C382 YES....Idle Shutdown Hot Ambient Au		
		N21500 C395 0.....Green House Gas Automatic En		
		N21530 C396 YES....Idle Shutdown Warning Period		
		N21540 C397 60....Idle Shutdown Warning Period		
		N21320 C399 100...Green House Gas Vehicle Spee		
		N21400 C400 474...Driver Initiated Override Re		
		N21420 C401 10....Green House Gas Vehicle Spee		
		N21330 C402 0.....Green House Gas Vehicle Spee		
2091120	S	EMUX Electronics Architecture	0	0
2091310	O	Engine Idle Shutdown Timer Disabled	0	0
2091315	O	Enable EIST Ambient Temp Overrule	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0
2092016	O	Typical Operating Speed 62 MPH	0	0
2092033	O	Powertrain Optimized for Balance Best analysis for vehicles where service includes frequent start and stop cycles.	0	0
2140200	O	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2140320	O	Remote Throttle & Wiring EOF Excludes Can Communication	180	4
2140410	S	Engine Brake Controls Located on RH Column	0	0
2140660	O	CARB Emission Compliant Engine	0	0

Price Level: August 1, 2025

100% Complete

Date: February 03, 2026

Deal: 27 MODA 589 SLPR 200

Quote Number: QUO-1235499-B9W2Q5

Printed On: 2/3/2026 2:46:18 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
2140700	S	EPA Engine Idling Compliance	0	0
2511470	O	320 Amp Alternator	1,436	15
2521090	S	Immersion Type Block Heater 110-120V Standard location is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0	0
2522110	O	PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	353	0
2538050	O	4 PACCAR Premium 12V Dual Purpose Batt 2920 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	328	62
2539410	O	Battery Jumper Terminal Mounted Under Hood LH Frame Rail. Not available with PX-7 engines.	147	4
2539716	O	CAB & SLPR POWER DISC SW MTD ON BBOX (KISSLING DISC SW 300A)	643	3
2539720	S	Low Voltage Disconnect System	0	0
2621000	O	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	167	0
2725270	O	37.4 CFM Naturally Aspirated Air Compressor X15 Only	258	27
2812170	O	Intebrate (Furnished on Engine) Features a dedicated cam lobe design for optimum power and three-stage engine brake operation.	0	0
2921110	O	PACCAR Fuel/Water Separator Standard Service PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	388	0
2921220	O	Fuel Heat for Fuel Filter	54	0
2921320	O	12V Heat for Fuel Filter Fuel filter heaters help ensure a seamless flow of diesel from the tank to the combustion chamber. Eliminating any possibility of moisture freezing within the fuel filter while simultaneously increasing the fuel temperature for atomization within the engine.	66	0
3010400	O	Engine Protection Shutdown w/ Label Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	7	0
3114270	S	High Efficiency Cooling System	0	0

Price Level: August 1, 2025

100% Complete

Date: February 03, 2026

Deal: 27 MODA 589 SLPR 200

Quote Number: QUO-1235499-B9W2Q5

Printed On: 2/3/2026 2:46:18 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 520 1242 sq in, 579 1325 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 567 1440 sq in, 589 1604 sq in.		
3212030	S	(2) 15" Premium SS Air Cleaners Cowl Mounted Slotted Stainless Steel Caps	0	0
3367240	U	Exhaust Dual SOC, LH SOC Stack	395	85
3381820	O	Chrome Exhaust Pipe(s) for Single Exhaust Requires stainless steel muffler guard/fairing (3381830), and Aftertreatment right-hand under cab.	107	7
3381830	O	Muffler Guard / Fairing Stainless Steel Half Round	166	7
3387880	O	7" Dia Chrome Plated Steel Standpipe(s) IPO 5"	242	4
3387890	O	36" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	80	4

Transmission & Equipment

4021920	O	Eaton RTLO20918B 18-Speed Includes oil-to-water cooler, rear transmission support, direct shift pattern. Synthetic lubricant to reduce friction, improve efficiency, & extend component life. Magnetic transmission oil drain plug captures & holds any metal fragments in transmission oil to extend service life. Torque limiting clutch brake. Forward ratios: LL-14.4, L-12.29, 1st-8.51, 2nd-7.26, 14th-1.00, 15th-0.86, 16th-0.73. Reverse ratios: R1-15.06, R2-12.85, R3-4.03, R4-3.43	1,373	343
4211530	O	SPL250 Lite HT Driveline, 2 Midship Bearings	2,551	190
4216330	O	SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles.	802	5
4250800	O	Manual Shifter, Chrome	-180	0
4256250	O	Heavy Duty Input Bearing for PTO Operation For use with Fuller RTLO transmission 1100 through 2250 series. The roller style input shaft bearing has twice the dynamic radial load capability of the ball bearing style and is recommended for transmissions that will be equipped with a transmission mounted 6 or 8 bolt PTO.	25	0
4321000	O	Self-Adjust Clutch	210	0
4380220	O	Pre-Damped Clutch	167	0

Price Level: August 1, 2025

100% Complete

Date: February 03, 2026

Deal: 27 MODA 589 SLPR 200

Quote Number: QUO-1235499-B9W2Q5

Printed On: 2/3/2026 2:46:18 AM



Sales Code	Std/Opt	Description	\$ List	Weight
		Pre-damped feature consists of a set of small springs around the hub, which dampen the engine torsional vibrations at idle speeds before they can reach the transmission and cause gear rattle. Option required on configurations specifying an ISX15 Family 1 engine and a manual transmission with torque ratings of 1650 lb-ft torque or higher.		
4380370	O	Remote Lube Hose For Release Bearing Mounted under hood left-hand rail	85	2
Air & Trailer Equipment				
4510210	O	Bendix AD-HF EP Air Dryer, Heater Coalescing filter, extended purge. Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	177	6
4520420	O	Pull Cords All Air Tanks	0	0
4540220	O	Wire Braid Brake Hose, Rear	363	15
4540260	O	Dash Winch Brake Switch To Operate All Brakes (Truck & Trailer). A&E EOF On Moveable Xmbr.	365	17
4540420	S	Nylon Chassis Hose	0	0
4543330	O	Polished Aluminum Air Tanks Outside Frame Rails Exposed air tanks outside the frame rails will be polished aluminum. Air tanks mounted inside the frame rails or covered by other components will be either painted aluminum (4543340) or painted steel (4543320) air tanks depending on air tank option selected.	417	0
4543500	S	Aluminum Air Tanks Natural under box, painted Back of Cab	0	0
4610925	O	Non-Self Returning Brake Hand Valve Dash mounted controls	239	0
4611930	O	Body Connections 5' BOC Junction box contains light and power circuits for body connections located 5' from back-of-cab	195	6
Tires & Wheels				
5054990	O	FF: MN 20ply 315/80R22.5 X Multi Z	1,535	68
5104610	O	RR: CN 16ply 11R24.5 HDL2 DL+	1,584	184
5190008	S	Code-rear Tire Qty 08	0	0
5220520	O	FF: Alcoa 89U637 22.5 X 9.00 High Polish Aluminum, Ultra ONE technology that saves more than 50 lbs. versus a comparable steel wheel. Built for refuse, logging, mining and other heavy haul applications that demand a tough wheel. Each wheel offers a 10,000 lbs. load rating.	654	-36
5320540	O	RR: Alcoa 98U637 24.5X8.25 High Polish	2,740	-120

Price Level: August 1, 2025

100% Complete

Date: February 03, 2026

Deal: 27 MODA 589 SLPR 200

Quote Number: QUO-1235499-B9W2Q5

Printed On: 2/3/2026 2:46:18 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		Aluminum, Ultra ONE technology.		
5390008	S	Code-rear Rim Qty 08	0	0
5409680	O	Schrader Double Sealing Extensions Schrader on tire valve extensions provide a seal against contaminants while extending the valve mouth for convenient access. Fits standard .305-32" valve cap threads. Maximum operating pressure, 150 psi.	43	0
Fuel Tanks				
5552100	O	26" Aluminum 70 Gallon Fuel Tank RH BOC Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	223	2
5554190	O	26" Aluminum 100 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	683	22
5602100	O	Location LH U/C 100 Gallon	0	0
5603070	O	Location RH BOC 70 Gallon	0	0
5612360	O	Aero Style Fuel Tank Step LH U/C Use with 26" 60 gallon or larger tanks	153	6
5650540	O	Polish (1) Non-Slip Fuel Tank Step, U/C Tank Only	29	0
5650820	O	Polish (2) Aluminum Fuel Tanks	502	0
5652830	O	Polish All Fuel / Hydraulic Tank Straps Does not apply to rectangular DEF tank straps	87	0
5652890	O	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0
5653000	O	Polished Stainless Steel Cover For DEF Tank	351	0
5653130	O	DEF To Fuel Ratio 1:1	0	0
5655019	S	DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal	0	0
Battery Box & Bumper				
6010670	O	Aluminum Space Saver Battery Box LH BOC Battery access from side	-130	-57
6030150	O	Rubber Battery Pad In Bottom of (1) Battery Box Mat in box that holds batteries only	13	4
6030540	O	Polish Battery/Tool Box(s) Aftertreatment Cab Entry, complete	298	0

Price Level: August 1, 2025

100% Complete

Date: February 03, 2026

Deal: 27 MODA 589 SLPR 200

Quote Number: QUO-1235499-B9W2Q5

Printed On: 2/3/2026 2:46:18 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6040610	O	Lower Battery Box(s) 4"	709	0
6121090	S	Steel Bumper Deep Tapered Chromed Two tow points	0	0
6132450	O	Heavy Duty External Tow Eye IPO Standard, N/A With FETPO	607	42
Cab & Equipment				
6510210	S	Aluminum Cab, 121" BBC Alum Hood SFFA With polished crown and spring tilt assist.	0	0
6540660	O	SmartSound Cab Insulation Package Cab acoustic insulation package for day cabs. Includes insulated inside firewall, top side floor damping, absorber treated kick panels, and insulated backwall and roof structure.	429	65
6540740	O	Peterbilt Keyless Entry The Peterbilt key fob functions to lock or unlock the vehicle. With a single click, the drivers door is locked or unlocked and with a double click all doors are locked or unlocked. The third button, depicted by a picture of a lamp, will start the exterior light self-test sequence, helpful when performing the daily pre-trip inspection.	162	2
6702130	O	44" Low Roof Sleeper w/Premier Interior	12,564	720
6800360	O	Rubber Fender Lips 2" Wide	493	6
6810035	O	Sleeper Walkthrough Curtain	192	5
6810245	O	Power Door Lock on Sleeper Door Required with Platinum Interior, Optional with Prestige Interior.	75	2
6810730	O	RH Sleeper Baggage Door Includes door-actuated baggage compartment light. Available on 44"/58"/72"/80" sleepers.	440	11
6811390	O	Coil Spring Mattress Width and length vary by sleeper size.	244	36
6812590	O	Polished Stainless Steel Sleeper Vents In place of painted vent.	158	0
6812790	O	LH Full Height Access Door With Vent	739	4
6814250	O	Thermal Insulation Pkg 44" & 58" Low Roof Sleeper The thermal insulation package is designed to make the compartment thermally efficient in extreme temperatures. Models 579 and 567 include thick closed-cell foam in the floor carpet and fiber insulation in the walls and roof structure.	112	0
6911740	O	Peterbilt LX Driver Peterbilt LX Air seat, high height backrest, adjustable seat track length, 2 chamber lumbar support, premium suspension with adjustable	181	3

Price Level: August 1, 2025

100% Complete

Date: February 03, 2026

Deal: 27 MODA 589 SLPR 200

Quote Number: QUO-1235499-B9W2Q5

Printed On: 2/3/2026 2:46:18 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		damping, auto leveling, exit air dump, memory for sitting height, fore-aft isolator with lockout, vinyl bellows over suspension, Requires folding armrests, side and back storage pocket. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress into cab and sleeper (knee sweep) with improved passenger side ingress/egress for personal cargo/luggage. Standard with fabric/vinyl finish - color coordinated with interior color		
6921130	O	Peterbilt LX Passenger seat Peterbilt LX Air seat, high height backrest, adjustable seat track length, 2 chamber lumbar support, premium suspension with adjustable damping, auto leveling, exit air dump, memory for sitting height, fore-aft isolator with lockout and vinyl bellows over suspension. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress into cab and sleeper (knee sweep) with improved passenger side ingress/egress for personal cargo/luggage. Standard with fabric / vinyl - color coordinated with interior color.	528	28
6930580	O	Drivers Armrests - LH & RH	170	4
6930590	O	Passenger Armrest - LH only Required with Evolution LX seats, optional with Evolution ST Seats.	125	2
6930800	O	Black Seat Color IPO Standard Color	0	0
6939080	O	Driver Seat Comfort Package Leather Only. Includes ventilation & heating system, adjustable side bolsters in seatback.	1,117	2
6939090	O	Passenger Seat Comfort Package Leather Only. Includes ventilation & heating system, adjustable side bolsters in seatback.	1,117	2
6939400	S	Air Ride Driver	0	0
6939420	S	High Back Driver	0	0
6939450	O	Leather Driver	320	0
6939500	O	Air Ride Passenger	0	0
6939520	S	High Back Passenger	0	0
6939550	O	Leather Passenger	319	0
7001520	S	Adjustable Steering Column - Tilt/Telescope	0	0
7001630	O	Premium Steering Wheel with Multi Function Premium Multi-functional Leather Wrapped Steering Wheel with Peterbilt logo over horn button. Includes audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	19	5
7033560	O	Platinum Interior - Alpine Gray	3,592	25



Sales Code	Std/ Opt	Description	\$ List	Weight
7040150	O	Rubber Floor IPO Carpet (Black Only) Rubber Floor Covering in Cab. Standard in Prestige interior, optional in Platinum/Premier interiors.	-88	0
7210200	O	Fixed Rear Window Back of Sleeper Dark Tint Includes curtains.	323	30
7230060	S	1-Piece Curved Windshield	0	0
7230360	S	Power Door Locks and Power Window Lifts Standard	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7322030	O	Sleeper Heater/Air Cond w/Controls in Sleeper for use w/44in sleeper.	1,316	41
7322130	O	Cup Holder (Floor Mounted) Includes two standard-size drink holders and one extra-large jugholder, coin tray, and clipboard-size storage area.	85	4
7410160	O	Outside Sunvisor - Stainless Steel V-Style Day cab / low roof sleepers.	977	8
7514050	S	Look Down Mirror Over Passenger Door with Black Housing	0	0
7516000	S	Stainless Steel Mirrors 7"X18" Heated & Motorized West Coast Style	0	0
7560860	S	(2) Convex 8 Inch Heated SSTL Mirrors Mounted under mirror brackets	0	0
7640050	O	(4) Air Horns 30" Chrome-Round Includes polished horn shields.	1,898	30
7721060	O	7" Infotainment Display Incl Apple Carplay	1,691	0
7725730	O	Premium Speaker Package For Cab (4) Speakers with 2 tweeters	515	6
7725785	O	Premium Speaker Package For Sleeper (2) Speakers with Amp; Available with 44 inch sleeper only.	428	8
7740140	O	Cobra 29 CB Radio Mounted Center Of Header Without weatherband. Mounted in center of header with sound tracker & illuminated panel. Includes wiring, microphone clip, & speaker. Must select antenna(s) option.	367	10
7748320	O	(2) 48" CB Antennas	193	1
7748500	O	CB Antenna Mounting, LH Mirror	20	0
7748510	O	CB Antenna Mounting, RH Mirror	20	0
7788335	S	Global Telematics Hardware	0	0
7850555	O	Dual USB Charging Port	211	2

Price Level: August 1, 2025

100% Complete

Date: February 03, 2026

Deal: 27 MODA 589 SLPR 200

Quote Number: QUO-1235499-B9W2Q5

Printed On: 2/3/2026 2:46:18 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
7851040	O	Removable Bugscreen Behind Grille	184	2
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7852050	O	Auto Reset Circuit Protection Daycab and Sleeper	20	0
7852080	O	Pull Out Tray/Work Surface Over Glove Box	243	3
7900070	O	Fire Extinguisher, Mounted In Sleeper Baggage Compartment, Hazmat approved UL listed/rated ABC	70	8
7900090	O	Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	33	13
7900950	O	Backup Alarm Wiring To BOC, 5 Ft Additional Wire	52	6
8011800	O	Drive Axle #1 Front Oil Temperature Gauge Located in Digital Cluster Display.	122	0
8011810	O	Drive Axle #2 Rear Oil Temperature Gauge Located in Digital Cluster Display.	116	0
8011830	S	Engine Oil Temperature Located in Digital Cluster Display.	0	0
8011850	O	Transmission Oil Temperature (Main) Located in Digital Cluster Display.	29	0
8012240	O	Guard(s) For Rear Axle Heat Gauge	69	2
8021800	S	Air Filter Restriction Pressure Gauge Located in Digital Cluster Display	0	0
8021810	S	Brake Application Air Pressure (Tractor) Located in Digital Cluster Display.	0	0
8021820	O	Brake Application Air Pressure (Trailer) Located in Digital Cluster Display	119	0
8021830	O	Increased Air Filter Full Indication For air filter restriction gauge	0	0
8021860	O	Suspension Air Pressure 1 (Load) Located in Digital Cluster Display	134	0
8021870	O	Suspension Air Pressure 2 (Load) Located in Digital Cluster Display, Plumbed to Firewall Bulkhead	134	0
8070110	O	(5) Additional Dash Switches with Wiring Located on dash panel C. Availability subject to dash space. Includes 4" 14 gauge wire with butt splice at rear of each additional switch.	213	2
8070390	O	Engine Hourmeter Gauge Located in Digital Cluster Display	0	0
8070810	S	Engine Manifold Pressure (Turbo Boost) Located in Digital Cluster Display	0	0
8070820	S	Engine Percent Torque Located in Digital Cluster Display	0	0
8070830	S	Main Instrumentation Panel	0	0

Price Level: August 1, 2025

100% Complete

Date: February 03, 2026

Deal: 27 MODA 589 SLPR 200

Quote Number: QUO-1235499-B9W2Q5

Printed On: 2/3/2026 2:46:18 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		Digital Cluster 15" Display includes: Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, and Voltmeter.		
8071190	O	Sleeper Digital Alarm Clock	183	2
8111210	O	Headlights LED Pod Integral Turn Signals	1,503	0
8121170	O	(5) Marker Lights, Bus LED Bullet	179	0
8131560	O	(2) Peterbilt Fog Lights Recessed in Bumper	114	6
8132210	O	(1) 6 in Spotlight, Round Halogen LH (1) 6" spotlight, round halogen left hand side.	109	4
8133115	O	Marker Switch Wiring FO Auxiliary Light The Marker Switch (located on the D-Panel) and wiring will be provided for furnish-by-owner auxiliary lighting underneath the cab/sleeper. For the models 567 and 579, a maximum of 10 amps is allowed. For the model 589, a maximum of 10 amps is allowed without the order of option 8133120.	34	2
8133120	O	Marker Switch Wiring FO Auxiliary Light The Marker Switch (located on the D-Panel) and wiring will be provided for furnish-by-owner auxiliary lighting on the dual air cleaners. A maximum of 10 amps is allowed without the order of option 8133115.	112	2
8133450	O	(2) Brackets F/O Beacon/Strobe, Roof Mounted (2) brackets for furnished by owner beacon / strobe lights roof mounted. Located above each door toward rear, includes switch and wiring.	120	4
8133630	O	Gravel Guard Stainless Steel For bumper mounted fog/driving lights	15	2
8134160	O	Self-Canceling Turn Signal	9	2
8140120	O	Incandescent Square Stop/Turn/Tail/Backup Left-hand / right-hand square end of frame or dropped a-brace	94	18
8140490	O	Additional LED Round Turn Signal Mirror mounted	184	5
8153050	O	(1) F/O Load Light, Switch, (2) 10' Wire Coils (1) furnished by owner load light, switch, (2) 10" wire coils, under cab/sleeper.	111	3
Paint				
8500710	O	Standard Paint Color Selection	-200	0
8530780	O	(1) Color Axalta Two Stage - Cab/Hood/Sleeper Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	897	0

Price Level: August 1, 2025

100% Complete

Date: February 03, 2026

Deal: 27 MODA 589 SLPR 200

Quote Number: QUO-1235499-B9W2Q5

Printed On: 2/3/2026 2:46:18 AM



Sales Code	Std/ Opt	Description	\$ List	Weight
		N85600 SLEEPER ROOF L0006EY WHITE		

Shipping Destination

Options Not Subject To Discount

9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	0
9407147	O	Fuel Price Index Factor \$0 NET	0	0
9408626	O	SmartLINQ RD - 5YR Sub Cummins Engines	799	0
9408707	O	Base Warr: Emissions (CARB Operation) 5YR/350K MI - X15 PER/PRO Engine	3,895	0
9408937	O	PDI After Body Upfit	0	0
9408982	O	Vehicle Layout Option is not subject to discount. Fleets will be split prior to build so that the charge is applied to only one unit. Quotes will not reflect this.	1,500	0

Miscellaneous

9409005	O	44in Sleeper / Platinum Interior (3P)	0	0
9409055	O	State Of Registry: California	0	0
9409641	O	Model Year 2026 Engine	0	0
9409749	O	2024 Series Emissions Engine	0	0
9409764	U	Disable Tractor Direction Indication	0	0

Promotions

Special Requirements

Special Requirement 1 0098010

Special Requirement 2

Special Requirement 3

Special Requirement 4

Fuel Efficiency Score:

Order Comments



Total List Price (W/O Freight & Warranty & Surcharges)	\$322,816
Marketing and Service Support Fee	\$1,725
Prepaid Freight	\$3,725
Total Surcharge/Options Not Subject To Discount	\$6,194
Total Weight (lbs)	20,272

Any price increase as the result of force majeure, rising costs of components (including but not limited to material shortages) or government tariffs are not included in the quoted price and will be the financial responsibility of the customer.

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: NONE

Final Destinations	Quantity
--------------------	----------