



Pblt Of Atlanta, Llc (P801)
172 Van Mar Blvd.
Jackson, Georgia 30233

MILLER INDUSTRIES
8503 Hilltop Dr
Ooltewah, Tennessee 37363
United States of America

David Marshall
Cell Phone:
Office Phone: (404)592-9980
Email: dmarshall@peteatlanta.com

VINCE TIANO

Vehicle Summary

Unit		Chassis	
Model:	Model 389	Fr Axle Load (lbs):	14600
Type:	Full Truck	Rr Axle Load (lbs):	40000
Description 1:	2022 389 SLPR V70	G.C.W. (lbs):	54600
Description 2:	200 CB		
Application		Road Conditions:	
Intended Serv.:	Wrecker	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	
Type:	Wrecker		6
Length (ft):	21	Wheelbase (in):	336
Height (ft):	13.5	Overhang (in):	90
Max Laden Weight (lbs):	1000	Fr Axle to BOC (in):	92.8
Trailer		Cab to Axle (in):	243.2
No. of Trailer Axles:	0	Cab to EOF (in):	333.2
Type:		Overall Comb. Length (in):	457
Length (ft):	0	Special Req.	
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	65		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
Base Model				
0003891	S	Model 389 April 1, 2021 Price Level will include the VMUX architecture and new dash, older price levels will continue to be the current model 389. See TSB 21-05 for additional information. The Model 389 embodies the Peterbilt heritage and merges it with a proven design to create a legendary classic for vocational applications. The lightweight, all-aluminum cab with lap seam construction, aircraft grade fasteners and bulkhead style doors is legendary for its durability. The pod-mounted headlamps are durable, corrosion-resistant and cost-effective to replace. Peterbilt's all-aluminum cab is not only extremely durable, it's also lightweight to allow for increased payloads to maximize performance and profitability.	188,869	14,915
0091200	S	Other Commodity	0	0
0093110	O	Wrecker Truck with recovery body used for recovering and towing stranded vehicles and equipment.	0	0
0095250	O	Wrecker A truck used to move disabled, improperly parked, impounded, or indisposed motor vehicle.	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200700	O	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0514360	O	10-3/4" Steel Rails 445-480" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	1,447	775
0601500	O	Full Steel Inner Liner	1,583	927
0611250	O	Heavy-Duty Iron Front Spring Brackets Forward and Rear	298	35
0620500	O	Frame Components Bolted IPO Huck Fastened	81	0
0633405	O	Additional Frame Drilling	499	0
0644090	O	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	-34	-64
0651090	O	Omit Rear Mudflaps and Hangers	-58	-25

Price Level: July 1, 2020
Deal: 2022 389 SLPR V70
Printed On: 2/12/2021 9:27:48 AM

Date: February 12, 2021
Quote Number: QUO-778928-X2F9D5



Sales Code	Std/ Opt	Description	\$ List	Weight
Front Axle & Equipment				
1011970	O	Dana Spicer D1461I 14,600 lb, 3.5 in. Drop Axle features an integrated air disc brake (IADB) knuckle to improve braking and reduce maintenance for IADB applications. The axles are designed for applications with a gross axle weight rating (GAWR) from 10,000 to 14,600 pounds. IADB feature eliminates separate torque plate and fasteners. One piece forged design includes tie rod arm, torque plate and spindle. The forged knuckle adds reliability for turn angles and the unique design features improved durability and camber alignment.	503	43
1112150	O	Taper Leaf Springs, Shocks 14,600 lb Hendrickson Taper Leaf Springs, shocks 14,6000 lb.	285	57
1233050	O	Power Steering TRW TAS85 TRW TA85 Power Steering for use with 14,600 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	366	7
1250180	S	Power Steering Reservoir Frame Mounted The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1354850	O	PHP10 Iron PreSet PLUS Hubs-Air Disc Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	52	42
1354870	O	Severe Service Disc Brake Rotor For refuse applications, providing the braking torque necessary to slow or stop the vehicle.	92	97
1380070	O	Greasable Front Spring Pins	78	0
1380290	S	Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0	0
1391380	U	10mm Front Spring Spacer Blocks	0	0
Rear Axle & Equipment				
1523310	O	Dana Spicer DSH40 40,000 lb, High Performance 40 Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	785	179
1616300	O	PHP10 Iron PreSet PLUS Hubs	-63	0
1616310	O	Severe Service Disc Brake Rotor	129	14

Price Level: July 1, 2020

Deal: 2022 389 SLPR V70

Printed On: 2/12/2021 9:27:48 AM

Date: February 12, 2021

Quote Number: QUO-778928-X2F9D5



Sales Code	Std/ Opt	Description	\$ List	Weight
		Severe Service Disc Brake Rotor for refuse applications.		
1680500	O	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	265	0
1680950	O	Stability System Not Selected Or Not Available	-61	0
1682430	O	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	-428	-30
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687040	O	Air Disc Rear Brakes, Tandem Drive Axle Includes Automatic Slack Adjusters.	1,652	0
1687090	O	Diff Lock Tandem Axles With Speed Interlock. Automatically Disengages Wheel Diff Lock at Speeds Above 25 mph.	1,937	60
1703900	O	Ratio 3.90 Rear Axle	0	0
1821640	U	Peterbilt Air Trac 46,000 lbs, 54in Axle Spacing	1,800	291
1920385	O	Air Springs, Internal Bumpers Air Trac / Air Leaf suspensions	59	0
1920450	O	Locate Single Leveling Valve Forward Drive Axle of Peterbilt Air Suspension (not avail with Low Air Leaf Susp or Low Low Air Leaf Susp)	46	0
1922260	O	Dash Mtd Dump Switch with Indicator Light Dash mounted dump switch with indicator light for suspension.	47	2

Engine & Equipment

2059921	O	X15 525@1900 GOV@1900 1850@1000 PERFORMANCE SERIES (2021 EMISSIONS)	8,871	292
		N21350 C121 75....Maximum Accelerator Vehicle		
		N21370 C128 75....Maximum Cruise Control Speed		
		N21460 C132 1100..PTO Maximum Engine Speed		
		N21520 C133 5.....Idle Shutdown Timer		
		N21610 C188 39....Idle Shutdown Cold Ambient A		
		N21630 C190 80....Idle Shutdown Hot Ambient Ai		
		N21510 C225 NO....Idle Shutdown with Parking B		
		N21450 C231 NO....Gear Down Protection		
		N21570 C233 YES....Idle Shutdown Manual Overrid		
		N21440 C234 NO....Engine Protection Shutdown		

Price Level: July 1, 2020
Deal: 2022 389 SLPR V70
Printed On: 2/12/2021 9:27:48 AM

Date: February 12, 2021
Quote Number: QUO-778928-X2F9D5



Sales Code	Std/Opt	Description	\$ List	Weight
		N21480 C238 NO....Cruise Control and Engine Br		
		N21470 C239 NO....Cruise Control Auto-Resume		
		N21590 C382 YES...Idle Shutdown Hot Ambient Au		
		N21530 C396 YES...Idle Shutdown Warning Period		
		N21540 C397 60....Idle Shutdown Warning Period		
		N21320 C399 120...Green House Gas Vehicle Spee		
		N21620 C189 60....Idle Shutdown Intermediate A		
		N21550 C206 35....Idle Shutdown Percent Engine		
		N21340 C209 120...Maximum Vehicle Speed		
		N21430 C333 0.....Driver Initiated OverrideMax		
		N21410 C334 0.....Driver Initiated Override Ma		
		N21500 C395 0.....Green House Gas Automatic En		
		N21400 C400 474...Driver Initiated Override Re		
		N21420 C401 10....Green House Gas Vehicle Spee		
		N21330 C402 0.....Green House Gas Vehicle Spee		
2091310	O	Engine Idle Shutdown Timer Disabled	0	0
2091315	O	Enable EIST Ambient Temp Override	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0
2092018	O	Typical Operating Speed 75 MPH	0	0
2092032	O	Powertrain Optimized for Performance Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0	0
2140150	O	Remote PTO and Throttle Provision 12-pin connector on engine harness.	67	0
2140200	O	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2140340	O	Remote EOF Throttle Control Plumbed Through Parking Brakes	215	4
2513070	O	200 Amp Alternator, Standard Brush Bosch Long Haul Extreme, standard brush, 170-200 Amps. Dual internal cooling fans, and externally-mounted rectifier and regulator.	172	0
2521090	S	Immersion Type Block Heater 110-120V Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0	0
2522110	O	PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	322	0

Price Level: July 1, 2020
Deal: 2022 389 SLPR V70
Printed On: 2/12/2021 9:27:48 AM

Date: February 12, 2021
Quote Number: QUO-778928-X2F9D5



Sales Code	Std/ Opt	Description	\$ List	Weight
2538050	O	4 PACCAR Premium 12V Dual Purpose Batt 2920 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	211	62
2539410	O	Battery Jumper Terminal Mounted Under Hood LH Frame Rail. Not available with PX-7 engines.	169	4
2539740	O	Kissling Battery Disconnect Switch, 300 amp Mounted on battery box	514	3
2621000	O	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	328	0
2725270	O	Naturally Aspirated 37.4 CFM Air Compressor X15 Only	334	27
2812170	O	Intebrake (Furnished on Engine) Features a dedicated cam lobe design for optimum power and three-stage engine brake operation.	0	0
2921110	O	PACCAR Fuel/Water Separator Standard Service PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	0	0
2921220	O	Fuel Heat for Fuel Filter	54	0
2921320	O	12V Heat for Fuel Filter Fuel filter heaters help ensure a seamless flow of diesel from the tank to the combustion chamber. Eliminating any possibility of moisture freezing within the fuel filter while simultaneously increasing the fuel temperature for atomization within the engine.	66	0
3010400	O	Engine Protection Shutdown w/ Label Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	6	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0	0
3211040	O	(2) 15" Premium SS Air Cleaners, Cowl Mtd SS Cap	1,907	68
3281280	O	Air Cleaner Locks For dual cowl mounted air cleaners	155	0
3365340	O	Exhaust Dual Side of Cab, LH Side of Cab Stack Aesthetic Only, DPF/SCR right-hand under cab	2,495	110
3381770	O	Curved Tip Standpipe(s)	52	1

Price Level: July 1, 2020
Deal: 2022 389 SLPR V70
Printed On: 2/12/2021 9:27:48 AM

Date: February 12, 2021
Quote Number: QUO-778928-X2F9D5



Sales Code	Std/ Opt	Description	\$ List	Weight
3381790	O	Chrome Finish Over Elbows for Dual Exhaust Requires DPF tool box right-hand under cab, and battery box left-hand under cab.	489	13
3381830	O	Muffler Guard/Fairing Stainless Steel Half Round	55	7
3387880	O	7" Dia Chrome Plated Steel Standpipe(s) IPO 5"	220	4
3387890	O	36" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	90	4

Transmission & Equipment

4022200	O	Eaton RTLO18918B 18-Speed Includes oil-to-water cooler, rear transmission support, direct shift pattern. Synthetic lubricant to reduce friction, improve efficiency, & extend component life. Magnetic transmission oil drain plug captures & holds any metal fragments in transmission oil to extend service life. Torque limiting clutch brake. Forward ratios: LL-14.4, L-12.29, 1st-8.51, 2nd-7.26, 14th-1.00, 15th-0.86, 16th-.073. Reverse ratios: R1-15.06, R2-12.85, R3-4.03, R4-3.43	3,465	120
4211530	O	SPL250 Lite HT Driveline, 2 Midship Bearings	1,379	190
4216330	O	SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles.	587	5
4250790	O	Aluminum Transmission Bell Housing IPO Iron Eaton transmission 1450 torque and above	67	-52
4250800	O	Manual Shifter, Chrome	123	0
4256250	O	Heavy Duty Input Bearing for PTO Operation For use with Fuller RTLO transmission 1100 through 2250 series. The roller style input shaft bearing has twice the dynamic radial load capability of the ball bearing style and is recommended for transmissions that will be equipped with a transmission mounted 6 or 8 bolt PTO.	24	0
4380220	O	Pre-Damped Clutch Pre-damped feature consists of a set of small springs around the hub, which dampen the engine torsional vibrations at idle speeds before they can reach the transmission and cause gear rattle. Option required on configurations specifying an ISX15 Family 1 engine and a manual transmission with torque ratings of 1650 lb-ft torque or higher.	166	0
4380270	O	Remote Lube Hoses For Clutch Linkage, Release Bearing and cross shafts, mounted to left-hand frame rail	312	6
4380360	O	Upgrade Clutch Torque Capacity Requires 1,550 or greater engine torque.	354	0

Air & Trailer Equipment

4510210	O	Bendix AD-HF EP Air Dryer, Heater Coalescing filter, extended purge. Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing	160	-2
---------	---	--	-----	----

Price Level: July 1, 2020

Deal: 2022 389 SLPR V70

Printed On: 2/12/2021 9:27:48 AM

Date: February 12, 2021

Quote Number: QUO-778928-X2F9D5



Sales Code	Std/Opt	Description	\$ List	Weight
		filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.		
4520420	O	Pull Cords All Air Tanks	8	1
4540220	O	Wire Braid Brake Hose, Rear	180	15
4540260	O	Wrecker AE Connection EOF On Moveable Crossmember Dash mounted air toggle valve plumbed to service brakes, 7-way socket (occupies the space of one gauge), winch brake switch on dash	500	17
4540420	S	Nylon Chassis Hose	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4543330	O	Aluminum Polished Air Tanks Outside Frame Rails Exposed air tanks outside the frame rails will be polished aluminum. Air tanks mounted inside the frame rails or covered by other components will be either painted aluminum (4543340) or painted steel (4543320) air tanks depending on air tank option selected.	275	0
4611930	O	Body Connections 5' BOC Junction box contains light and power circuits for body connections located 5' from back-of-cab	191	6
Tires & Wheels				
5058030	O	FF: MN 16ply 12R22.5 XZE Efficiency Rating: Fair All-position radial with extra-wide, extra-deep tread designed to help deliver wear in high scrub regional and line haul applications. Diameter= 42.6 inches; SLR= 19.8 inches	654	52
5166630	O	RR: BR 16ply 11R24.5 M726ELA Efficiency Rating: Poor Diameter= 44.2 inches; SLR= 20.6 inches	1,756	256
5190008	S	Code-rear Tire Qty 08	0	0
5220520	O	FF: Alcoa 89U637 22.5 X 9.00 High Polish Aluminum, Ultra ONE technology that saves more than 50 lbs. versus a comparable steel wheel. Built for refuse, logging, mining and other heavy haul applications that demand a tough wheel. Each wheel offers a 10,000 lbs. load rating.	496	-36
5320540	O	RR: Alcoa 98U637 24.5X8.25 High Polish Aluminum, Ultra ONE technology.	1,616	-120
5390008	S	Code-rear Rim Qty 08	0	0

Price Level: July 1, 2020
Deal: 2022 389 SLPR V70
Printed On: 2/12/2021 9:27:48 AM

Date: February 12, 2021
Quote Number: QUO-778928-X2F9D5



Sales Code	Std/ Opt	Description	\$ List	Weight
5407640	O	FF: Mirror Polish Wheels, Outer Surface Single/tandem steer. Mirror Polish outer surface of outer wheel. Without chrome wheel nuts.	73	0
5407660	O	RR: Mirror Polish Wheels, Outer Surface, Tandem Drive Mirror polish outer surface of outer wheels (4). Without chrome wheel nuts.	565	0
5409680	O	Schrader 1126 Double Seating Extensions Schrader on tire valve extensions provide a seal against contaminants while extending the valve mouth for convenient access. Fits standard .305-32" valve cap threads. Maximum operating pressure, 150 psi.	39	0
Fuel Tanks				
5552070	S	26" Aluminum 60 Gallon Fuel Tank RH BOC Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	0	0
5554160	O	26" Aluminum 90 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	551	20
5602090	O	Location LH U/C 90 Gallon	0	0
5603060	S	Location RH BOC 60 Gallon	0	0
5650540	O	Polish (1) Non-Slip Fuel Tank Step, U/C Tank Only	29	0
5650820	O	Polish (2) Aluminum Fuel Tanks	557	0
5652830	O	Polish All Fuel / Hydraulic Tank Straps Does not apply to rectangular DEF tank straps	83	0
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0
5652980	S	DEF To Fuel Ratio Between 1:1 And 2:1	0	0
5653000	O	Polished Stainless Steel Cover For DEF Tank	204	0
5655019	S	DEF Tank Small 11.1 Gallon Capacity	0	0
Battery Box & Bumper				
6010670	O	Aluminum Space Saver Battery Box LH BOC Battery access from side	38	-20
6030150	O	Rubber Battery Pad In Bottom of (1) Battery Box Mat in box that holds batteries only	12	4
6030540	O	Polish Battery/Tool Box(s), Aftertreatment Cab	325	0

Price Level: July 1, 2020
Deal: 2022 389 SLPR V70
Printed On: 2/12/2021 9:27:48 AM

Date: February 12, 2021
Quote Number: QUO-778928-X2F9D5



Sales Code	Std/Opt	Description	\$ List	Weight
		Entry complete		
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6121090	S	Steel Bumper Deep Tapered Chromed Two tow points	0	0
6132450	O	Heavy Duty External Tow Eye IPO Standard	789	42

Cab & Equipment

6510140	S	Alum Cab 123in BBC Alum Hood SFFA fenders w/polished crown, spring tilt assist. Proprietary anti-blow-down locking mechanism that keeps hood open during servicing & prevents unintentional closing. Hood latch each side secures hood to cowl. Proprietary all-alum cab is light weight & durable for long service life. One-piece roof reduces potential for leaks. Two-piece windshield for cost effective windshield replacement. Lap seam construction & aircraft fasteners has greater clamp load than rivets. Bulkhead style doors provide virtually water-tight, rattle-free performance. Extruded alum door frames for strength & durability. Full length, heavy-duty piano-type stainless steel door hinges & pins provide durability. View window in RH door for safety. Electric windshield wipers & washers w/intermittent wiper function. Grab handles mtd on cab LH & RH for cab access. Convex mirror over RH door & below each rear view mirror for improved visibility & safety.	0	0
6540660	O	SmartSound Cab Insulation Package Cab acoustic insulation package for day cabs. Includes insulated inside firewall, top side floor damping, absorber treated kick panels, and insulated backwall and roof structure.	409	65
6540740	O	Peterbilt Keyless Entry The Peterbilt key fob functions to lock or unlock the vehicle. With a single click, the drivers door is locked or unlocked and with a double click all doors are locked or unlocked. The third button, depicted by a picture of a lamp, will start the exterior light self-test sequence, helpful when performing the daily pre-trip inspection.	167	2
6701780	O	44" Low Roof Sleeper w/Prestige Interior Includes single LH full-length door, storage tray, door actuated baggage compartment light, rubber floor mats in baggage compartment, sleeper curtain, rubber floor covering, bunk restraint, wide walk-through opening with upholstered cover, cab/sleeper air suspension, 31 in x 78.5 in coil spring mattress, single dome light, fluorescent light, 12V DC power outlet, HVAC Air Filter, (2) two-way vents, and local reading/spot light LH above bunk.	8,639	720
6800360	O	Rubber Fender Lips 2" Wide	116	8
6810240	O	Power Lock on Sleeper Door For use with Prestige Sleeper Interior only. The power sleeper door lock is standard in Platinum Sleeper Interior.	47	2
6810730	O	RH Sleeper Baggage Door	333	10

Price Level: July 1, 2020
Deal: 2022 389 SLPR V70
Printed On: 2/12/2021 9:27:48 AM

Date: February 12, 2021
Quote Number: QUO-778928-X2F9D5



Sales Code	Std/ Opt	Description	\$ List	Weight
		Includes door-actuated baggage compartment light. Available on 44"/58"/72"/80" sleepers.		
6812590	O	Polished Stainless Steel Sleeper Vents In place of painted vent.	37	0
6814250	O	Thermal Insulation Pkg 44" & 58" Low Roof Sleeper The thermal insulation package is designed to make the compartment thermally efficient in extreme temperatures. Models 579 and 567 include thick closed-cell foam in the floor carpet and fiber insulation in the walls and roof structure. Models 389, 386, 384, 367 and 365 include thick closed-cell foam in the floor and special mylar-faced foam in the walls and roof structure.	35	4
6911710	O	National Premium Driver Seat Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	331	4
6921710	O	National Premium Passenger Seat Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	539	4
6930580	O	Drivers Armrests - LH & RH	95	4
6930590	O	Passenger Armrest - LH only Required with Evolution LX seats, optional with Evolution ST Seats.	47	2
6930800	O	Black Seat Color IPO Standard Color	0	0
6939400	S	Air Ride Driver	0	0
6939420	S	High Back Driver	0	0
6939450	O	Leather Driver	256	0
6939500	O	Air Ride Passenger	387	43
6939520	S	High Back Passenger	0	0
6939550	O	Leather Passenger	256	0
7001610	O	Leather Steering Wheel	127	0
7039220	O	Platinum Interior - Arctic Gray Platinum Interior - Arctic Gray offers striking charcoal A & B instrument panels and high-gloss burlwood C & D instrument panels, monochromatic color-coordinated dash that is glare-resistant, charcoal soft-touch upper, bright bezel on gauges, high-gloss burlwood insert on contoured doorpads with vinyl inserts, left hand and right hand door mounted map pockets with built-in courtesy lights, power windows & door locks on both doors, adjustable steering column with 18" soft-touch steering wheel, soft-touch steering column cover, floor carpet, padded premium vinyl headliner w/insert, (2) inside sunvisors (integral vanity mirrors), (2) coat hooks, (2) dome/reading lights, footwell lighting, integrated "dead pedal", (5) inside entry grab handles, cupholder & map bin in dash, 12V power outlet dash mounted, and Peterbilt SmartNav	3,819	33

Price Level: July 1, 2020
Deal: 2022 389 SLPR V70
Printed On: 2/12/2021 9:27:48 AM

Date: February 12, 2021
Quote Number: QUO-778928-X2F9D5



Sales Code	Std/Opt	Description	\$ List	Weight
		System (occupies the space of six gauges). Includes SmartNav Audio System. SmartNav and associated options DO NOT apply to Glider Kits.		
7040150	O	Rubber Floor IPO Carpet (Black Only) Rubber Floor Covering in Cab. Standard in Prestige interior, optional in Platinum/Premier interiors.	-34	-6
7210200	O	Fixed Rear Window Back of Sleeper Dark Tint Includes curtains.	168	30
7230350	O	2-Piece Flat Windshield	34	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7322030	O	Sleeper Heater/Air Cond w/Controls in Sleeper for use w/44in sleeper.	1,079	41
7322130	O	Cup Holder (Floor Mounted) Includes two standard-size drink holders and one extra-large jugholder, coin tray, and clipboard-size storage area.	97	4
7330700	S	Peterbilt Comfort Control - Cab	0	0
7330710	O	Peterbilt Comfort Control - Sleeper	139	2
7410040	O	Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper.	436	4
7561180	O	Aero Mirrors Ea Side Htd & Mtrzd 4-Way Adjustable Bright Finish with Convex	565	4
7610800	O	(4) Round Air Horns Chrome-(2) 30" & (2) 37.5" with polished horn shields.	1,410	33
7725740	O	Midlevel Speaker Package For Cab (4) Speakers	205	6
7725775	O	Midlevel Speaker Package For Sleeper (2) Speakers; Available w/44 inch sleeper only.	153	5
7740100	O	Cobra 40 Channel CB Radio w/Integral Speaker Includes illuminated front panel	251	11
7748500	O	CB Antenna Mounting, LH Mirror Available with Rami only on 1.9m, available without Rami on medium duty	20	0
7748510	O	CB Antenna Mounting, RH Mirror Available with Rami only on 1.9m, available without Rami on medium duty	20	0
7748650	O	RAMI Multiband Antenna System - Dual Includes (2) 48 inch antennas.	141	4
7788055	S	SmartLINQ Remote Diagnostics SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault	0	0

Price Level: July 1, 2020
Deal: 2022 389 SLPR V70
Printed On: 2/12/2021 9:27:48 AM

Date: February 12, 2021
Quote Number: QUO-778928-X2F9D5



Sales Code	Std/Opt	Description	\$ List	Weight
		coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesn't require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine.		
7788058	O	24 Months SmartLINQ Subscription Cummins Engines.	0	0
7850210	O	Plug-In Auto Reset Circuit Breaker in place of fuses in junction box.	109	0
7851040	O	Removable Bugscreen Behind Grille	180	2
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7900070	O	Fire Extinguisher, Mounted In Sleeper Baggage Compartment, Hazmat approved UL listed/rated ABC	60	8
7900090	O	Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	18	13
7900950	O	Backup Alarm Wiring To BOC, 5 Ft Additional Wire	55	6
8011100	O	Main Transmission Temperature Gauge 52mm Round, backlit. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	45	0
8011140	O	Engine Oil Temperature Located in SmartNav display	0	0
8011150	O	Main Transmission Oil Temperature Located in SmartNav display	21	0
8011220	O	Axle Temperature Gauges, Tandem Drive	170	2
8011390	O	Engine Oil Temperature Gauge	36	0
8012240	O	Guard(s) For Rear Axle Heat Gauge	64	2
8021050	O	Air Restriction Pressure Gauge 52mm Round, backlit. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	190	0
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall	0	0
8022150	O	Fuel Filter Restriction Gauge	136	0
8032420	O	Buzzer On Air Suspension Dump Valve Requires dash mounted dump valve (1922260)	11	0
8070120	O	Manifold Pressure, Boost	0	0

Price Level: July 1, 2020
Deal: 2022 389 SLPR V70
Printed On: 2/12/2021 9:27:48 AM

Date: February 12, 2021
Quote Number: QUO-778928-X2F9D5



Sales Code	Std/Opt	Description	\$ List	Weight
		Located in SmartNav display		
8070170	O	DPF Status	0	0
		Located in SmartNav display		
8070180	O	Fuel Economy	0	0
		Located in SmartNav display		
8070190	O	Percent Torque	0	0
		Located in SmartNav display		
8071020	O	Manifold Pressure Gauge	43	2
8071280	O	Suspension Pressure Gauge	61	2
8071870	S	Main Instrumentation Panel, Graphics Display	0	0
		Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights with audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.		
8072560	O	(1) Additional Dash Switch With Wiring	56	0
		(1) additional dash switch with wiring. Spare 1 and 2 share 15 amp fuse, spares 3, 4, and 5 share 15 amp fuse. Availability subject to dash space.		
8111140	S	Headlights Projector Module Pod	0	0
		Integral Turn Signals		
8121170	O	(5) Marker Lights, Bus LED Bullet	175	0
8131560	O	(2) Peterbilt Fog Lights	148	6
		Recessed in bumper		
8132210	O	(1) 6 in Spotlight, Round Halogen LH	131	4
		(1) 6" spotlight, round halogen left hand side.		
8133110	O	Switch & Wiring F/O Auxiliary Light	69	2
		Under cab/sleeper (15 amp max), includes switch on the dash that will power metri-pack sealed connections at the left-hand / right-hand side of cab at base of the firewall. Bundle panel light harness break outs with firewall harness.		
8133120	O	Switch & Wiring F/O Aux Light On Air Cleaners	117	2
		Includes switch on the dash which will power metri-pack sealed connections at the left-hand / right-hand air cleaner outlets		
8133450	O	(2) Brackets F/O Beacon/Strobe, Roof Mounted	245	4
		(2) brackets for furnished by owner beacon / strobe lights roof mounted. Located above each door toward rear, includes switch and wiring.		
8133500	O	Switch On Dash For Light In Sleeper	35	2
		In addition to standard switch		
8133630	O	Gravel Guard Stainless Steel	77	0

Price Level: July 1, 2020
Deal: 2022 389 SLPR V70
Printed On: 2/12/2021 9:27:48 AM

Date: February 12, 2021
Quote Number: QUO-778928-X2F9D5



Sales Code	Std/ Opt	Description	\$ List	Weight
		For bumper mounted fog/driving lights		
8140120	O	Incandescent Square Stop/Turn/Tail/Backup Left-hand / right-hand square end of frame or dropped a-brace	49	9
8153100	O	(1) F/O Load Light, Switch, 10' Wire Coil Under / in cab / sleeper baggage compartment	48	2

Paint

8500710	O	Standard Paint Color Selection	-200	0
8530780	O	(1) Color Axalta Two Stage - Cab/Hood/Sleeper Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE N85720 SK FAIRINGS L0006EY WHITE N85600 SLEEPER ROOF L0006EY WHITE	763	0

Shipping Destination

Options Not Subject To Discount

9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	0
9408936	O	Frame Layout Identical to Previous Chassis	475	0

Miscellaneous

9409005	O	44in Sleeper / Platinum Interior (3P)	0	0
9409831	S	2021 EPA Emissions Engine Warranty Only	0	0